



**SURFACE PREPARATION PRODUCTS**

# FASTSTRIP PLUS

## SOLVENT ACRYLIC SEALER REMOVAL



View More Info for this Product at  
<http://www.surecretedesign.com/fast-strip-plus/>

# FASTSTRIP PLUS

## SOLVENT ACRYLIC REMOVAL

### DESCRIPTION

**FastStrip Plus** is a high-powered, solvent-based stripper for heavy coatings and the most difficult to remove sealers. Specially formulated to be used indoors or out, wherever water can be used to flush off the sealer. **FastStrip Plus** contains biodegradable surfactants and non-chlorinated solvents.

### APPLICATION

**FastStrip Plus** may be sprayed from a Chapin sprayer, brushed, or poured on and squeegeed evenly across the surface to be treated. Test in a small area before applying **FastStrip Plus** across the complete area.

Apply at the rate of approximately 1 gallon per 150 ft<sup>2</sup> (13.9 m<sup>2</sup> per 3.8 L). Allow **FastStrip Plus** to stand for a minimum of 20 – 30 minutes to soften coating. Add a small amount of water and scrub vigorously to emulsify the coating. Heavy coatings may require a second treatment. Scrape up residue and store for disposal, rinse thoroughly with water. Flush away dissolved residue or vacuum up and rinse clean.

Exercise caution for creating a source of ignition with electrical tools, fuel burning appliances, and other sources, as **FastStrip Plus** is flammable. Use protective gear including respirator and provide proper ventilation.

### CLEAN-UP

Before **FastStrip Plus** dries; spills and tools can be cleaned up with water.

### DISPOSAL

Contact your local government household hazardous waste coordinator for information on disposal of unused product.

### LIMITATIONS

For use by trained professionals that have read the complete SDS.



### PACKAGING

5 gal (18.9 L) pails

### COVERAGE

Approx. 150 ft<sup>2</sup> per gal. (13.9 m<sup>2</sup> per 3.8 L).

### PHYSICAL PROPERTIES

**Appearance:** straw color

**Odor:** solvent

**VOC:** 0 g/L

### SHELF LIFE

Under normal conditions: when kept dry and moisture free, out of direct sunlight, the shelf life of an unopened container is (12) months from the date of purchase. Storage must be under roof and off the floor. Avoid temperature extremes. Rotate inventory to maintain product that is within limits.

### WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price, or replacement of product (if defective), at manufacturer's/seller's option. SureCrete Design Products shall not be liable for cost of labor or direct and/or incidental consequential damages.

### CAUTIONS

**KEEP OUT OF REACH OF CHILDREN.** **Inhalation:** Avoid prolonged breathing of product. Use NIOSH approved respirator if threshold limit values are unsafe. **Skin Contact:** Skin contact may cause irritation. Remove contaminated clothing and wash affected skin with soap and water. Launder clothing before reuse. If symptoms persist, seek medical attention. **Eyes:** Wear safety eye protection when applying. Contact with eyes may cause irritation. Flush eyes with water for 15 minutes. If symptoms persist, seek medical attention.

### SAFETY DATA SHEETS

The following are links to all available safety data sheets related to this product:

- <http://www.surecretedesign.com/sds/surface-prep-fast-strip-plus-sds.pdf>